## **AMENDMENTS TO THE CLAIMS**

## **Claims**

- 1. (Currently Amended) A method of transmitting in time slots in TDMA frames user data in bursts of GSM format, each burst comprising data portions separated by a training sequence, the method comprising transmitting <u>only</u> data of a first user in a first data portion of a burst before the training sequence and <u>only</u> data of a second user in a second data portion of the burst after the training sequence.
- 2. (Previously Amended) The method of claim 1 including transmitting each data portion in a sub time-slot allocated to a different user.
- **3.** (Previously Amended) The method of claim 2 comprising transmitting user data in each time slot in a burst structure, including transmitting user data in each sub time slot in a corresponding burst structure.
- **4.** (Previously Amended) The method of claim 3 in which a burst structure has n bits, the method including partitioning each time slot into m sub time slots, and transmitting user data in each sub time slot in a corresponding burst structure having n/m bits.
- **5.** (Previously Amended) The method of claim 3 in which the user data comprises speech.
- **6.** (Previously Amended) The method of claim 1 in which the TDMA system is an EDGE packet switched network.
- 7. (Previously Amended) The method of claim 6 in which the TDMA system is a wireless system, the method including encoding, in up-link, data from p users such that each forms 1/p of an RLC/MAC block, wherein the data from each user is encoded into a respective one of p sub-time-slots.

- **8.** (Previously Amended) The method of claim 7, including transmitting the RLC/MAC block over four TDMA frames.
- 9. (Previously Amended) The method of claim 1 including encoding the user data into an RLC/MAC block for transmission, and transmitting the RLC/MAC block in a sub-time-slot over a plurality of frames.
- **10.** (Previously Amended) The method of claim 1 including encoding user data associated with at least two users into a single RLC/MAC block, and transmitting the portions of the RLC/MAC block associated with respective users in respective sub-time-slots.
- 11. (Previously Amended) The method of claim 1 including transmitting the user data in each time slot in a burst structure having n bits, partitioning each time slot into m sub time slots, and transmitting user data in each sub time slot in a corresponding burst structure having n/m bits.
- **12.** (Previously Added) The method of claim 11 in which the user data comprises speech.
- **13.** (Previously Amended) The method of claim 12 in which the TDMA system is a wireless system, the method including encoding, in up-link, data from p users such that each forms 1/p of an RLC/MAC block, wherein the up-link data from each user is encoded into a respective one of p sub-time-slots.
- **14.** (Previously Amended) The method of claim 1, including transmitting the RLC/MAC block is over four TDMA frames.